



SUB118

EUROPEAN COMPONENTS
DIRECT REFLECTION SUBWOOFER
HIGH SPL AND POWER HANDLING
CLEAN AND DEEP

欧洲低音单元
直接反射式低音箱
高声压及功率持续力
清晰深沉的低音
适合大型演出、酒吧、家庭影院、豪华KTV使用

AT A GLANCE

Real 1200W RMS power capacity (8 hours pink noise)

Clean and deep reproduction

Premium custom made European driver

Impressive 60mm peak-peak excursion capacity

Heavy braced, vibration free birch plywood cabinet

Touring grade soft touch gloss-free black painting

APPLICATIONS

The SUB118 subwoofer is suitable for bass reinforcement for main PA systems, touring or permanent installations for small to large stages, indoor or outdoor live performances.

Suitable in spaces like:

- Stadium and arena
- Multi-functional room
- Auditorium and Theater
- Night club
- Bar
- High-end Karaoke room

SPECIFICATIONS

Power Capacity / Puissance admissible (35~350Hz pink noise 8 hours)	1200W RMS / 2400W program
Nominal impedance / Impédance nominale	8Ω
Frequency response / Réponse en fréquence (-6dB half space, no EQ)	35~500Hz
Average Sensitivity / Sensibilité moyenne	99dB/W/m (40~150Hz)
Calculated Maximum Pressure / Pression acoustique maximale (SPL / 1m)	129dB continuous / 132dB program
Nominal Directivity / Directivité nominale (-6dB)	Omidirectional in usable range
Recommended low cut filter / Coupe bas conseillé	30Hz 24dB/oct
Low Frequency driver / Haut parleur de grave	Custom made European 18" driver, Ferrite magnet, 4" voice coil, 60mm peak-peak excursion capacity
Crossover / Filtre acoustique	No, only use in active mode with external electronic crossover
Flying hardware / Équipement d'accroche	No
Connectors / Connectique	2x NEUTRIK Speakon® NL4MP (1+/1- Input & Link, 2+/2- Link)
Pole mount / Support pour pieds	20mm thread top hat
Cabinet / Caisse	CNC made with tongue and groove assembly all made with 18mm birch plywood
Finish / Finition	Touring grade textured black mat coating
Size / Taille (WxHxD)	590x660x605mm
Weight / Poids	49kg net, 55kg gross

VIEW

